

Part System 零件編碼

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Type 類型	Series 系列名稱	Rated Voltage 額定電壓	Capacitance 靜電容量		Capacitance Tolerance 靜電容量容許差		Product Characteristics 產品要求	Case Size 尺寸	Lead Type 腳型	Material Type 材料類型							
Type Radial Lead	Code T	Voltage Code	Capacitance (μF)	Code	Capacitance Tolerance	Code	Product Characteristics	Code	See Below	See Below	See Below						
		6.3V 0J	0.1	R10	0~+20	A	PET sleeve and Pb free lead wire										
		10V 1A	0.22	R22	-20-0	B	Standard	K									
		16V 1C	0.33	R33	-15~+20	C	Special	Other Letters									
		25V 1E	3.3	3R3	-25~+20	D											
		35V 1V	4.7	4R7	-3~+10	E											
		50V 1H	22	220	-30~+20	F											
		63V 1J	33	330	+10~+20	G											
		80V 1K	47	470	+20~+40	H											
		100V 2A	100	101	-10~+10	K											
		160V 2C	220	221	-20~+20	M											
		200V 2D	330	331	-10~+20	Y											
		220V 2P	470	471													
		250V 2E	1000	102													
		350V 2V	2200	222													
		400V 2G	3300	332													
		420V W6	4700	472													
		450V 2W	6800	682													
		470V 2Y	8200	822													
		500V 2H	10000	103													
		550V 2M	22000	223													
		600V 2S															

1. Radial lead type

(1) Case size 尺寸(11~15)

Case size	Code	Case size	Code	Case size	Code	Case size	Code	Case size	Code	Case size	Code
4 x 7	04070	8 x 16	08160	10 x 40	10400	12.5 x 40	12400	16 x 20	16200	18 x 35.5	1835M
5 x 11	05110	8 x 20	08200	10 x 50	10500	12.5 x 45	12450	16 x 25	16250	18 x 40	18400
6.3 x 7	06070	10 x 10.5	1010M	12 x 50	11500	12.5 x 50	12500	16 x 30.5	1630M	18 x 45	18450
6.3 x 11	06110	10 x 12.5	1012M	12.5 x 15	12150	13 x 50	13500	16 x 35.5	1635M	18 x 50	18500
6.3 x 15	06150	10 x 16	10160	12.5 x 20	12200	14.5 x 20	14200	16 x 40	16400	20 x 25	20250
8 x 10.5	0810M	10 x 20	10200	12.5 x 25	12250	14.5 x 25	14250	18 x 20	18200	20 x 40	20400
8 x 11.5	0811M	10 x 25	10250	12.5 x 30.5	1230M	14.5 x 30.5	1430M	18 x 25	18250	22 x 30	22300
8 x 15	08150	10 x 30.5	1030M	12.5 x 35.5	1235M	16 x 18.5	1618M	18 x 30.5	1830M	22 x 40	22400

(2) Configurations 腳型(16~17)

Configurations腳型	ΦD	16	17	SPEC規格	Remark
Long lead 長腳	4Φ~18Φ	L	L	-	
Cutting 切腳	4Φ~18Φ	C	K	3.5±0.5	Lead length
		C	Q	5.0±0.5	Lead length
Forming Tape 成型編帶	4Φ~8Φ	T	C	5.0+0.8/-0.2	Lead to Lead Distance
Straight Tape 直型編帶	5Φ	R	T	2.0+0.8/-0.2	Lead to Lead Distance
	4Φ~5Φ	Y	A	2.5+0.8/-0.2	Lead to Lead Distance
	6.3Φ~8Φ	R	A	2.5+0.8/-0.2	Lead to Lead Distance
	8Φ	R	B	3.5+0.8/-0.2	Lead to Lead Distance
	D≥10Φ	R	C	5.0+0.8/-0.2	Lead to Lead Distance
	D≥10Φ	R	E	5.0+0.8/-0.2	Lead to Lead Distance

*RC=continuous taping

*RE=discontinuous taping

(3) Material type 材料類型(18)

Material type 材料類型	Code
Flat rubber and nonvent case 平面柏梗無防爆外殼	1
Convex rubber and nonvent case 凸面柏梗無防爆外殼	2
Flat rubber and vent case 平面柏梗防爆外殼	3
Convex rubber and vent case 凸面柏梗防爆外殼	5